



## STS700 BATTERY TESTER



### Overview

#### STS700 BATTERY TESTER

cod. 804243

Digital tester to check the status of the battery, the starting efficiency (CCA), the starter system and the alternator circuit of the vehicle.

Selectable international standards both for cars and motorbikes, which correspond to different starting current ranges used by the battery manufacturer.

Handy and small in size, it can operate on 12V batteries (WET, GEL, MF, AGM, PbCa, EFB) both disconnected and connected to the vehicle, making testing operations quick and easy.

The colour graphic display makes the product intuitive and easy to use.













It is possible to graphically display the performance of the battery voltage over time.

Saving and printing of reports via PC connection.

Features:

- for WET, GEL, MF, AGM, PbCa, EFB batteries from 8-240 Ah at 12V;
- tests performed: battery status, starting capability (CCA), starter system, vehicle alternator circuit;
- selectable reference standards for cars and motorbikes;
- tests can be performed with the battery disconnected or connected to the vehicle;
- color graphic display;
- graphic display of voltage performance over time;
- multilingual: EN, IT, FR, DE, ES, RU, PT, NL, PL, JP, CN, KO;
- saving and printing of reports via PC connection.

### Technical data

 CODE	CODE 804243		CURRENT RANGE 100/1400-IEC-DIN A		CURRENT RANGE 12N5.5-4A,12N5.5A-3B (MOT) A
	CHARGING VOLTAGE 12 V		CURRENT RANGE 26A17/245H2-JIS A		OPERATING TEMPERATURE (MIN-MAX) 0 - 40 $\bar{A}$ , $\bar{A}$ °C
	BATTERY CAPACITY 8-240 Ah		CURRENT RANGE 200/2000-SAE A		DIMENSIONS 8,0 x 2,3 x 15,0 cm
	CURRENT RANGE 185/1125-EN A		CURRENT RANGE 100/2000-CA(MCA)- CCA-BCI A		WEIGHT 0,27 kg