

### Thermic 2W PRO 13 H

### Thermic 2W PRO 13 L



**NEW**



**T.V.** Thermal Valve



#### Standard equipment:

- 0.966.0083 Gun M22 - 3/8 with rotating coupling.



- 0.966.0084 Lance M22 high/low pressure



- 0.966.0090 Ceramic 350 bar nozzle type 045



- 0.966.0086 High pressure hose 10 m



#### Optional:

- Hose reel kit cod. 0.966.0062 hose included (15 m)
- 0.966.0082 ROTOX lance 255 bar
- 5.012.0319 Suction hose with check valve



#### Equipped with:

- 1450 RPM reducer between engine and pump.
- Self-priming CL5 Lavor pump, 3 ceramic pistons, brass pump head and unloader valve flanged • Suction and delivery S. S. valves.
- Unleaded gasoline engine 13 HP **Honda** GX 390 (Thermic 2W PRO 13 H)
- Unleaded gasoline engine 13 HP **Loncin** G 390F (Thermic 2W PRO 13 L)
- 5 litres detergent tank with filter and cap • Readily serviceable suction water filter
- Oil-alert safety device for engine protection • Glycerine pressure gauge.
- Folding handle with aluminium hinges • Ø 300 big pneumatic wheels; easy to handle also up and down steps and over uneven ground • S/S pump cover on request

	Thermic 2W PRO 13 H	Thermic 2W PRO 13 L
code	0.066.0036	0.066.0037
operat. pressure	250 bar-3625 psi	250 bar-3625 psi
delivery rate	1080 l/h-4.76 GPM	1080 l/h-4.76 GPM
engine type/hp	Honda GX 390/13	Loncin G 390F/13
pump type/RPM	CL5/1450 RPM	CL5/1450 RPM
max. water inlet temp.	60 °C	60 °C
dimension/weight	85x58x105cm / 65 Kg - 143 lbs	85x58x105cm / 65 Kg - 143 lbs